



# RadiForce® GS320

54 cm (21.3") Monochrome LCD Monitor



Optimum Image, Same Image.



12:41



# 3MP RadiForce® GS320

54 cm (21.3") Monochrome LCD Monitor

In continuously striving for the highest-level of safety and quality while contributing to long-term cost reduction, EIZO offers a five-year limited warranty.

5 Year Warranty

5

The product shall be free from defects in material and workmanship for a period of five (5) years, but subject to the usage time being 40,000 hours or less from the date of purchase.

- 10-bit (1,024 tones) from a 13-bit look-up table (8,161 tones) can be displayed simultaneously for high-definition medical imaging.
- Digital Uniformity Equalizer (DUE) provides optimum uniformity of the backlight's luminance.
- CAL Switch function offers calibration modes that can be selected for any specific image such as CR and CT from a front panel button.
- Backlight Saver helps to reduce power consumption during prolonged usage.
- Independent Image Setting (IIS\*) allows for any specific area of an image to be adjusted and pre-set to various grayscale gradation and luminance levels. \*Bundled ScreenManager Pro for medical required.
- Compatible with EIZO's remote calibration device "Clip-On Swing Sensor G1" using EIZO's quality control software RadiCS and RadiNET Pro. *Compatible with RadiCS and RadiNET Pro versions 2.5.0 and later.*



Model Variations	GS320-CL: Clear Base GS320-CL-P: Pairing	USB Ports / USB Standard	1 upstream, 2 downstream / Standard Rev. 2.0
Cabinet Color	Black	Power Requirements	AC100 - 120V, 200 - 240V: 50/60 Hz
Panel	54 cm (21.3") TFT Monochrome LCD Panel (IPS)	Power Consumption	115 W
Active Display Size (H x V)	324.8 x 433.1 mm	Power Save Mode	Less than 3 W
Viewable Image Size	Diagonal: 541 mm	Sensor	Backlight Sensor
Native Resolution	1536 x 2048	Power Management	DVI DMPM
Pixel Pitch	0.2115 x 0.2115 mm	OSD Languages	English, French, German, Italian, Japanese, Simplified Chinese, Spanish, Swedish, Traditional Chinese
Grayscale Tones	1,024 from a palette of 8,161 tones	Height Adjustment Range	82 mm
Viewing Angles (H,V)	170° / 170°	Pivot	90°
Brightness	1000 cd/m <sup>2</sup> (typical)	Tilt / Swivel	40° Up / 35° Right, 35° Left
Recommended Brightness for Calibration	450 cd/m <sup>2</sup>	Dimensions (W x H x D)	With Stand: 376 x 522.5 - 604.5 x 208.5 mm Without Stand: 376 x 500 x 92 mm
Brightness Uniformity	DUE Function	Net Weight	With Stand: 9.9 kg Without Stand: 6.9 kg
Contrast Ratio	850: 1 (typical)	Hole Spacing	VESA standard (100 x 100 mm)
Response Time	23 ms (typical)	Certifications and Standards	CE (Medical Device Directive), TÜV/GM (EN60601-1), cTUVus (UL60601-1, CSA C22.2 No. 601-1), CB (IEC60601-1), VCCI-B, FCC-B, Canadian ICES-003-B, c-Tick, FDA 510(k)
Scanning Frequency (H,V)	31 - 100 kHz, 48 - 71.5 Hz (VGA Text: 69 - 71 Hz) Frame synchronous mode: 59 - 61 Hz	Supplied Accessories	AC power cord, user's manual, signal cable (DVI-D-DVI-D), USB cable, EIZO LCD Utility Disk (ScreenManager Pro for Medical software), warranty card
Dot Clock	165 MHz		
Input Signals	DVI Standard 1.0		
Input Terminal	DVI-D 24 pin		



## EIZO NANAO CORPORATION

153 Shimokashiwano, Hakusan, Ishikawa 924-8566 Japan  
Phone +81-76-277-6792 Fax +81-76-277-6793

radiforce.com

Specifications are subject to change without notice.

All product names are trademarks or registered trademarks of their respective companies. RadiCS and RadiNET are trademarks, and EIZO and RadiForce are registered trademarks of Eizo Nanao Corporation.