

Complete Card Reading Solutions





- Powered USB bus—no external power supply required.
- Hardware compatible with any computer or terminal with an USB interface
- Single, dual or three track capability
- Bi-directional read capability
- Reads encoded cards that meet ISO/ANSI/CDL/AAMVA standards
- Up to 1,000,000 passes with ISO-conforming cards
- Includes USB interface cable
- USB HID class vendor-defined MSR emulation or keyboard emulation
- Available in black or white



Specifications

OPERATING

Reference Standards:

ISO, ANSI, CDL and AAMVA

Power Input:

From USB

Recording Method:

Two-frequency coherent phase (F2F)

Message Format:

Vendor defined emulation

Card Speed:

3 to 50 IPS

MTBF:

Electronics: 125,000 hours Head: 1,000,000 passes

Ordering Information

Track 2, pearl white	P/N 21040105
Track 1 & 2, pearl white	P/N 21040103
Track 1, 2 & 3, pearl white	P/N 21040101
Track 2, black	P/N 21040106
Track 1 & 2, black	P/N 21040104
Track 1, 2 & 3, black	P/N 21040102

Dimensions:

MECHANICAL

Length: 3.94" (100mm) Width: 1.28" (32,5mm) Height: 1.23" (31,3mm)

Weight:

Reader with cable: 5.8 oz. (1,65g)

Connector:

USB

ENVIRONMENTAL

Temperature:

Operating: 32°F to 131°F (0°C to 55°C) Storage: -22°F to 158°F (-30°C to 70°C)

Humidity:

Operating: 10% to 90% noncondensing Storage: Up to 100% noncondensing

Altitude:

Operating: 0-10,000 ft. (0-3,048m) Storage: 0-50,000 ft. (0-15,240m)



20725 S. Annalee Avenue Carson, CA 90746 Phone: (310) 631-8602 Fax: (310) 631-3956

Internet: http://www.magtek.com

1-888-624-8350