

## All In One POS Terminal

## PT-6215



The PT-6215 All-In-One POS Terminal is the complete solution for small to medium businesses. Designed from the ground up by Partner Tech to be an affordable and easy to use terminal for today's business owner, the PT-6215 offers a system of fully integrated features that make it the only true All-In-One POS terminal on the market. The compact, space saving design of the terminal features an integrated thermal receipt printer, customer display, large 15" touch screen, and an integrated MSR reader. All of these features packed into a compact terminal allows for space saving reliability in any environment.



PT-6215 rear view

| Item                   | PT-6215                                                                                                                              |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| CPU                    | Intel Atom N270 @ 1.6 GHz / 512k L2 cache                                                                                            |
| Chipset                | Intel 945 GSE + ICH7M                                                                                                                |
| Memory                 | Standard DDR2 1GB, supports up to 2GB                                                                                                |
| LCD                    | 15" TFT LCD                                                                                                                          |
| Resolution             | 1024 x 768                                                                                                                           |
| Touch                  | 5-wire Resistive touch                                                                                                               |
| LCD Brightness         | 250 nit (w/o touch)                                                                                                                  |
| LAN                    | 10/100/1000 Mbps onboard Ethernet controller                                                                                         |
| Storage                | SATA 3.5" hard drive or optional SATA SSD                                                                                            |
| I/O Ports              | 4 x COM ports<br>1 x RJ11 port (+24v)<br>1 x PS2 Keyboard port<br>1 x RJ-45 LAN port<br>5 x USB ports<br>1 x DC +12V<br>1 x VGA port |
| OS                     | WEPOS / POSReady / Windows XP Pro / Windows XP Embedded                                                                              |
| Adaptor                | AC 100V ~ 240V / DC12V power adaptor                                                                                                 |
| Operating Temperature  | 32° F ~ 104° F                                                                                                                       |
| Storage Temperature    | -4° F ~ 140° F                                                                                                                       |
| Operating Humidity     | 15% ~ 80%                                                                                                                            |
| Storage Humidity       | 15% ~ 80%                                                                                                                            |
| Dimensions             | 13.5" (W) x 12.6" (D) x 10" (H)                                                                                                      |
| Integrated Peripherals | Triple track magnetic card reader<br>2" x 20" VFD customer display<br>3.14" thermal receipt printer with auto cutter                 |
| Options                | RFID module<br>WIFI module                                                                                                           |

10010110

